



Oxygen Meter – Online Oxygen Meter% MODEL – OLPD-100

Online Oxygen Analyser are designed for accurate and reliable measurement of Oxygen in Air, Nitrogen, Argon, etc. These are based on state of art Galvanic Oxygen Sensors, and provide fast response. They require no periodic maintenance like replacing electrodes or electrolyte and can be calibrated using ambient air or standard calibration samples. A digital LED display provides direct percentage output readout. The power Source is a 230Volt ac. Model OLPD 100 online for continues Oxygen Monitoring with 4 to 20mA and alarm output are available Monitor for general applications

SPECIFICATIONS

- ◆ **Range** : 0 –25.% with Resolution 0.1% Model - OLPD- 25
- ◆ **Range** : 0 –100% with Resolution 0.1% Model - OLPD- 100
- ◆ **Additional Range** : 0 -19.99% with Resolution 0.01% %
- ◆ **Operating Temp.:** 10 °C to 45 °C
- ◆ **Accuracy** : +/-1% full scale
- ◆ **Response Time** : 90% in less than 25 Seconds (From low to high)
- ◆ **Display** : 3 ½ LED
- ◆ **Sensor Type** : Electromical type (Imported)
- ◆ **Sensor life** : 1 Year Estimated
- ◆ **Power Source** : 230-Volt Ac.
- ◆ **Output** : Output-- 4 to 20 mA. & Adjustable single Alarm
- ◆ **Cabinet** : DIN panel mount box with separate sensor unit
- ◆ **Dimensions of Cabinet;** 96x96x 150mm
- ◆ **Weight** : 1 kg. App.

APPLICATIONS

- ◆ Gas purity check
- ◆ Oxygen Plant
- ◆ Gas separation Plant
- ◆ Cylinder filling
- ◆ Inert Gas Purging

Also available -:

- ◆ Direct reading Nitrogen Purity meter (W.R.T. Oxygen as impurity) for 90.0% to 100.0% Nitrogen Purity designed for Nitrogen plant online operation and control.
- ◆ PPM Oxygen Meter with Resolution 0.1ppm reading for U.H.P. Nitrogen.
- ◆ Dedicated economy model are available.
- ◆ We can also design and development dedicate d analyser on OEM base
- ◆ The interest of continued product development we reserve the right to change the specification without prior notice

SPECIAL FEATURES.

- ◆ Fast response
- ◆ Easy to read Display
- ◆ Output-- 4 to 20 mA
- ◆ Alarm Relay contact
- ◆ Accurate, Disposable Micro Fuel Sensor.



252-D Amar Gian Industrial Estate, L..B.S. Marg, Khopat, Thane (W) 400 6
Maharashtra, India Tel. +91 (022) 2547 49 01 Telefax : 2547 58 68
Email : hemaki@bom5.vsnl.net.in Web site : www.hemaki.com